

ELECTRONIC PINBRAZING UNIT

SAFETRACK S30 COMPACT

Introduction

S30 Compact is a small pinbrazing unit made especially for cathodic protection installation. Electronically controlled. Powered by three batteries.

Technical Specifications

Voltage	36V DC
Number of brazings/charge	40 – 60
Unit weight inc. batteries	20kg
Dimensions L*W*H* (mm)	315*220*400

Delivered with:
Gun S3, PB 9303
Battery Box, PB 9325
Electronic Unit, PB 9326
Earthing Device, PB 8067



ACCESSORIES



Batteries, open cell, 18 Ah
PB 8088 (3 pcs)



Battery Charger,
stationary use
36V DC, PB 8050



High power batteries, sealed,
13 Ah, PB 8092 (3 pcs)

High power batteries, sealed,
16 Ah, PB 8093 (3 pcs)



Battery Charger, car
use 12/36V DC, PB
8055

Grinding machine 36V DC
PB 8055



Tungsten Carbide burrs
Carrying Harness, PB 9523
Extension cables









S4 Automatic gun,
PB 9102




PINBRAZING CONSUMABLES

Brazing Pins & Ferrules

DESIGN	ITEM	Part No.
 ø8mm	General pins	
	Standard	10051
	with extra brazing alloy	10101
 ø9.5mm	Standard	10131
 M8	Threaded pins with self locking stainless steel nut and two washers	
	Standard Brass	10641
 M10	Standard Brass	10741
 M12	Threaded pins with two brass nuts and one stainless steel spring washer	
	Standard Brass	10561
	Ferrules for pin dia.	
	8mm	2003
	9.5mm	2009
	M8, M10, M12	2012

All the above pins are available with fuse wire

Cable Lugs & Sleeves

		Cable Lugs for direct brazing of cable and sleeves for smaller cables	
No.	Description	No.	Description
6056	Cable Lug for 10mm sq, direct	6700	Copper Sleeve for 2.5mm ² , cable
6065	Cable Lug for 16mm sq, direct	6701	Copper Sleeve for 4.0mm ² , cable
6080	Cable Lug for 25mm sq, direct	6702	Copper Sleeve for 6.0mm ² , cable (all above for use with 6056 lug)
6081	Cable Lug for 35mm sq, direct		
6079	Cable Lug for 50mm sq, direct		



Corrpro Companies Europe Limited
 Adam Street, Bowsfield Lane, Stockton on Tees, TS18 3HQ
 Telephone: (01642) 614106 (8 lines) Telex: 587388
 Fax: (01642) 614100 E-mail: ccel@corrpro.co.uk